ROHS




- コンデンサー等の電子部品の絶縁にご利用できます。
- ケーブルや電線の端末の保護、防塵、防湿にご利用できます。
- パイプのネジ部の保護、内部の防塵、防湿にご利用できます。

材 質 軟質PVC 標準材: SS108

標準色 黒(04)

●ご注文時は、品番末尾に色番号(-04)を付けてください。



品 番		寸 法(mm)			包装単位
		φd	L	t	(個)
*	VCP- 1.4	1.4	10±1	0.8 ± 0.3	
	VCP- 2	2	10±1	1.0 ± 0.3	
*	VCP- 2.4	2.4	10 ± 1	1.0 ± 0.3	
*	VCP- 2.7	2.7	10 ^{±1}	1.0 ± 0.3	
	VCP- 3	3	10 ^{±1}	1.0 ± 0.3	
*	VCP- 3.3	3.3	10±1	1.0 ± 0.3	
*	VCP- 3.5	3.5	10±1	1.0 ± 0.3	
	VCP- 4	4	10±1	1.0 ± 0.3	
*	VCP- 4.7	4.7	10 ^{±1}	1.0 ± 0.3	
*	VCP- 5	5	15 ^{±1}	1.0 ± 0.3	
*	VCP- 5.5	5.5	15 ^{±1}	1.0 ± 0.3	1 000
	VCP- 6	6	15 ^{±1}	1.0 ± 0.3	1,000
*	VCP- 7.5	7.5	15±1	1.0 ± 0.3	
	VCP- 8	8	15 ^{±1}	1.0 ± 0.3	
*	VCP- 9	9	20 ± 1	1.0 ± 0.3	
	VCP-10	10	20 ± 1	1.0 ± 0.3	
	VCP-12	12	20 ± 1	1.0 ± 0.3	
*	VCP-13	13	20 ± 1	1.0 ± 0.3	
	VCP-14	14	30 ± 1	1.5 ± 0.4	
*	VCP-15	15	30 ± 1	1.5 ± 0.4	
	VCP-16	16	30 ± 1	1.5 ± 0.4	
	VCP-18	18	30 ± 1	1.5 ± 0.4	
	VCP-20	20	30 ± 1	1.5 ± 0.4	
*	VCP-22	22	40 ± 1	1.5 ± 0.4	500
*	VCP-24	24	40 ± 1	1.5 ± 0.4	
*	VCP-26	26	40 ± 1	1.5 ± 0.4	250
*	VCP-28	28	40 ± 1	1.5 ± 0.4	250

品 番		寸 法(mm)			包装単位
		φd	L	t	(個)
*	VCP-30	30	50 ± 1.5	1.5 ± 0.4	050
*	VCP-32	32	50 ± 1.5	1.5 ± 0.4	250
*	VCP-34	34	50 ± 1.5	$1.5^{\pm0.4}$	200
*	VCP-36	36	50 ± 1.5	1.5 ± 0.4	200
*	VCP-38	38	60 ± 1.5	1.7 ± 0.4	
*	VCP-40	40	60 ± 1.5	1.7 ± 0.4	100
*	VCP-42	42	60 ± 1.5	$1.7^{\pm0.4}$	
*	VCP-44	44	60 ± 1.5	1.7 ± 0.4	
*	VCP-46	46	70±2	$2.0^{\pm 0.5}$	
*	VCP-48	48	70±2	2.0 ± 0.5	50
*	VCP-50	50	70±2	2.0 ± 0.5	
*	VCP-52	52	70±2	$2.0^{\pm 0.5}$	
*	VCP-54	54	80±2	2.0 ± 0.5	
*	VCP-56	56	80±2	2.0 ± 0.5	20
*	VCP-58	58	80±2	$2.0^{\pm 0.5}$	30
*	VCP-60	60	80±2	$2.0^{\pm 0.5}$	
*	VCP-62	62	90±2	$2.0^{\pm 0.5}$	
*	VCP-64	64	90±2	$2.0^{\pm 0.5}$	
*	VCP-66	66	90±2	$2.0^{\pm 0.5}$	
*	VCP-68	68	90±2	$2.0^{\pm 0.5}$	
*	VCP-70	70	100±2	2.0 ± 0.5	20
*	VCP-72	72	100±2	$2.0^{\pm 0.5}$	20
*	VCP-74	74	100±2	$2.0^{\pm 0.5}$	
*	VCP-76	76	100±2	$2.0^{\pm 0.5}$	
*	VCP-78	78	100±2	$2.0^{\pm 0.5}$	
*	VCP-80	80	100±2	$2.0^{\pm 0.5}$	

※印は受注生産品(数量については別途ご相談ください。)

下記材料による製品は受注生産品です。詳細はお問い合わせください。

材質 UL規格認定材(E58538): SS107UFTT



SU® UL224認定品 E55167

Cat.No. 20 SS107UFTT······定格105℃, 600V



(CSA規格認定品) LR52853 · LR52854

Cat.No. 20 SS107UFTT····· 定格 90℃, 300V

SHINAGAWA SHOKO CO.,LTD.